

BigPak®

40x48D TP-TC

Thermoformed HDPE
Twin Sheet Construction

Interlocking
Pallet and Cover



01 / Details

FEATURES

- Peanut lock provides unit security and eliminates need for stretch wrapping
- Interlocking pallet and cover for secure stacking
- Large leg footprint
- Lower cost alternative vs. rigid alternatives

OPTIONS

- One or multiple stripes in 48" direction
- Wide range of pallet stripe colors
- With or without Ever-Lock2®
- Leg drain holes
- Custom logos



Twin-Sheet Thermoformed



Plastic



Peanut Lock



Nestable Conveyable Pallet



Nestable Conveyable Cover



Fiberboard Z-fold


02 / Specifications

PRODUCT	DESCRIPTION	DIMENSIONS			WEIGHT	COLOR	RATINGS		STACK HEIGHT	QTY PER STACK		QTY 53' TLD	QTY 40' SC	QTY 40' HC
		L	W	H			FORK	FLOOR		STD.	HC			
BP4048D TP	Twin Sheet Pallet	48" 1,219 mm	40" 1,016 mm	5.875" 149.23 mm	20 lbs 9.07 kg	Black	1,200 lbs 545 kg	7,500 lbs 1,409 kg	100" 2,540 mm	40	44	1,200/ 30 Skids	800/ 20 Skids	880/ 20 Skids
BP4048D TC	Twin Sheet Cover	48" 1,219 mm	40" 1,016 mm	3.5" 88.9 mm	14 lbs 6.35 kg	Black	1,200 lbs 545 kg	7,500 lbs 1,409 kg	100" 2,540 mm	40	44	1,200/ 30 Skids	800/ 20 Skids	880/ 20 Skids

Performance characteristics vary with applications. To optimize nominal specifications, loads must be evenly distributed to reach capacity. Load construction, support conditions, transportation, load retention, user facility and temperature are factors that affect pallet capacity.

Big Pak[®] 40x48D TP-TC

SPECIFICATIONS



PALLET ADVANTAGES

- Environmentally Friendly
- ISPM 15 Exempt
- Long Service Life



Easy
Clean



Sanitary



Weather
Resistant



Impact
Resistant



4-Way
Forklift/jack
Entry



Recycle

TriEnda publishes standard guidelines for its products, based on its testing standards, and, as such, these guidelines do not constitute any warranty related to each customer's individual application. The material handling industry has not standardized on test methodology and rating criteria for each individual product. All TriEnda products are sold with the understanding that the customer will validate for themselves the suitability of the product for their specific application. As each product application is unique, the customer assumes all risks associated with the determination and actual use of the pallet.

