

PRODUCT DETAILS AND SPECIFICATIONS

BULKHEAD SPACERS Fill large voids for maximum

Fill large voids for maximum weight loads quickly and reliably

01 / Details

Ideal to use in:

Cargo Protect+ products fully absorb the force of the load to deliver the best freight damage prevention and weight balance compliance in the industry.

- The nose end of trailers and containers to properly balance axle weight
- The center of rail car shipments to fill large longitudinal void
- Both ends of intermodal containers to brace the load from shifting

REDUCES DAMAGES BY UP TO 80%

> INREASES PRODUCT QUANTITY PER SHIPMENT





Durable design for rail shipments



Patented Interlocking System



Slides Easily Into Place

02 / Specifications

Truck Bulkhead Spacer

- 48"h x 36"w x 16"d 29 lbs
- 1 assembly set spaces 30" deep
- Compliant with CFR 49
- Withstands 20,000 lbs of force
- Can fit 544 pieces or 272 sets in return shipments
- Adaptable to many load patterns
- Parts are nestable for return shipments

Rail Bulkhead Spacer


- 102"h x 39"w x 16.5"d 55 lbs
- 1 assembly set spaces 30" deep
- AAR approved
- Withstands 41,000 lbs of force
- Can fit 336 pieces or 168 sets in return shipments
- Adaptable to many load patterns
- Parts are nestable for return shipments

BULKHEAD SPACERS

FEATURES



- Energy absorbing- cushions without crushing
- Lightweight rigid parts enable fast loading
- Ergonomic hand holes ensure easy handling
- Splinter-free & lightweight HDPE material reduces dock related injuries
- Weather & moisture resistance allows outside storage to optimize warehouse space
- Easy to clean surfaces are beneficial for use with a variety of commodities



CARGO PROTECT+ ADVANTAGES

- Environmentally Friendly
- ISPM 15 Exempt
- Long Service Life



Clean



Sanitary



Weather Resistant



Impact Resistant



Recycle

TriEnda publishes standard guidelines for its products, based on its testing standards, and, as such, these guidelines do not constitute any warranty related to each customer's individual application. The material handling industry has not standardized on test methodology and rating criteria for each individual product. All TriEnda products are sold with the understanding that the customer will validate for themselves the suitability of the product for their specific application. As each product application is unique, the customer assumes all risks associated with the determination and actual use of the pallet.



CONTACT US

N7660 Industrial Road Portage, WI 53901 www.trienda.com | sales@trienda.com 1-800-356-8150

